

The Radar Decision Guide

HOW TO CHOOSE THE RIGHT WEATHER RADAR BAND,
CONFIGURATION, AND SITE FOR YOUR ENVIRONMENT



Weatherproof Your World.

baronweather.com

No two environments are the same and neither is the radar that serves them best. The right match means decades of high-resolution data, reliable early warnings, and a system built to last. The wrong one means coverage gaps, degraded data when it matters most, and a system that is ultimately unreliable for your needs.

This guide gives decision-makers a clear, practical framework for selecting the right radar covering frequency band, transmitter type, power, dual-polarization, and site selection. Whether you are building a new network from scratch, expanding coverage, or upgrading aging infrastructure, these are the considerations that matter most.

Start Here: Which Radar Is Right for You?

If you need a fast orientation before diving into the technical detail, the table below maps common operational situations to the most appropriate radar starting point. Every deployment is ultimately unique, but this gives you a confident foundation for the conversation with your radar partner.

Your situation	Recommended starting point
Tropical / sub-tropical region, frequent heavy rain or flooding	S-Band — lowest rain fade, longest QPE range, ideal for early warning systems
General national meteorological network, broad coverage needed	C-Band — best balance of performance, range, and cost; most globally deployed
Mobile deployment or research applications	X-Band — compact, transportable, high short-range precision
Gap-fill in existing network	C-Band — proven for targeted coverage deployments
Mountainous or complex terrain	Transportable C-Band ; Baron site survey recommended
Dual-polarization required (hail, tornado, flood extent)	Any band — Baron offers dual-pol across S, C, and X; higher power recommended

Baron's radar team and engineers are available to support your selection and perform site surveys before any purchase. No two environments are identical, and expert consultation at the outset prevents costly errors downstream.

Transmitters and the Local Weather Environment

All weather radars work on the same fundamental principle: transmitting radio frequency (RF) pulses into the atmosphere, then analyzing the signal reflected back by precipitation, wind, and other atmospheric material. The characteristics of that returned signal allow the radar processor to calculate the location, intensity, and type of hydrometeors with precision.

The transmitter is the engine of that process. There are three main types in operational use today, and the choice among them has meaningful implications for data quality, longevity, and total cost of ownership.

Klystron

The klystron is the gold standard for high-performance weather radar. A large, high-power vacuum tube used in C and S-band systems, it is renowned for signal stability — the characteristic that enables accurate wind (velocity) data and effective removal of ground clutter from buildings, terrain, and cellular towers.

Klystrons power the U.S. NEXRAD network and are capable of operating for 20 or more years with proper maintenance. They perform reliably across all weather scenarios: heavy rain, hail cores, tornadic signatures, flooding events, and winter precipitation. For agencies that need the highest-quality data and the longest operational lifespan, the klystron is the benchmark.

Magnetron

Magnetrons also use vacuum tube technology and represent an excellent balance between performance and budget. Paired with solid-state modulation and digital signal processing components, magnetron-based radars are highly effective in most meteorological environments and particularly capable at detecting the fine hydrometeor detail that matters for precipitation classification and intensity estimation.

For organizations that require strong operational capability without the capital commitment of a klystron system, the magnetron is a proven and widely deployed solution. Baron's C-band and X-band magnetron radars include proprietary technologies that mitigate the inherent limitations of the magnetron transmitter.



Figure 1 - Klystron

Solid-State Transmitters

Modern solid-state transmitters, built on gallium-nitride (GaN) power amplifiers, now deliver the range, sensitivity, and resolution once associated with high-power klystron and magnetron systems without the high-voltage components, consumable tubes, and maintenance those technologies require. For many operational and research deployments, solid-state is no longer a compromise. It is the preferred choice.

A solid-state transmitter produces lower peak power than a tube-based system, but peak power alone does not determine how far or how clearly a radar sees. Baron's solid-state radars use long-pulse transmission with dynamic matched filtering to recover the detection sensitivity of a far higher-power system. Baron's patented Progressive Pulse Compression Plus (PPC+) technique, developed in partnership with the University of Oklahoma, eliminates the traditional near-range blind spot without additional hardware or fill pulses delivering consistent, calibrated data from close range to the edge of coverage.

Reliability is built into the architecture itself. With eight field-replaceable GaN amplifier modules, extensive built-in monitoring, and no high-voltage components or consumable tubes to service, solid-state systems offer markedly lower maintenance demands over the life of the system. And if a single module fails, the radar keeps running — a meaningful operational advantage for agencies that cannot afford downtime during severe weather.


Power: Why It Matters More Than You Might Think

Transmitter power has a greater effect on what a radar can see than most people expect. A well-powered system reveals the lighter precipitation at the outer fringes of a storm system in Figure 2, giving forecasters earlier warning and better situational awareness. This is especially critical in coastal environments, where tropical systems, dry lines, and offshore convection need to be detected far enough out to allow meaningful response time.

Additionally, more power is beneficial for the split-beam configuration of dual-polarization systems, as shown in Figure 3. Unlike conventional horizontal-scanning radars, these systems split the radar signal between



350,000 Watts



1,000,000 Watts

Figure 2

two polarizations, effectively halving the power of each transmit channel. More information on dual-polarization radar is provided later in this document.

For other situations, especially single-polarization systems, a 350 kW system will deliver strong, reliable performance. This type of radar is powerful enough to analyze localized weather events, providing meteorologists with situational awareness and accurate information.




Figure 3

Frequency: Choosing Your Band

Frequency — the radar’s “band” — is one of the most important technical decisions in radar selection. It determines the range, resolution, sensitivity, and how well the system performs during heavy precipitation, particularly the phenomenon known as rain fade (signal attenuation). X-Band and C-Band signals are more sensitive due to a shorter wavelength, while the S-band’s longer wavelength makes it far less susceptible to rain fade or attenuation.




Figure 4

S-Band (2.8–3.5 GHz)

S-band radar operates at the lowest frequency of the three main bands and is the least susceptible to attenuation. In environments with frequent heavy rain, tropical convection, or significant flooding risk, this resistance to rain fade is not a technical nicety, it is operationally critical. S-band systems maintain accurate detection through the most intense precipitation events, at ranges up to 460 km.

S-band also delivers a substantial advantage in velocity data quality. Due to the physics of lower frequency signals, S-band produces significantly better storm tracking and wind data than C or X-band – a meaningful edge for agencies that rely on accurate velocity information for severe weather detection, tornado identification, and early warning decision-making.

Historically in the United States, S-band radar was restricted to federal government use. Since 2014, private and academic entities have had access to high-frequency S-band spectrum licenses, opening this capability to a much broader range of organizations globally. The compact small S-band configuration offers the power and performance of full S-band in a significantly reduced infrastructure footprint.

- **Best for:** tropical and sub-tropical regions, flooding and early warning systems, long-range national networks
- **Transmitter:** klystron (up to 1 MW) or magnetron
- **Typical range:** 460 km observation, 230 km QPE

C-Band (5.4 GHz)

C-band is Baron's most widely deployed radar solution worldwide, and for good reason. It delivers a highly capable balance between performance and cost: excellent range, strong sensitivity, flexible deployment options including fixed and transportable configurations, and broad applicability across meteorological environments.

C-band does experience more attenuation than S-band in heavy precipitation, a known limitation that Baron addresses directly through advanced signal processing and attenuation correction technologies. For organizations building or expanding a general-purpose meteorological network, C-band is almost always the right place to start.

- **Best for:** national and regional networks, general meteorological surveillance, versatile operational environments
- **Transmitter:** klystron (1 MW) or magnetron (350 kW), or solid-state
- **Typical range:** 230 km observation, 115 km QPE

X-Band (9.5 GHz)

X-band radar operates at the highest frequency, offering the finest resolution of the three bands. This narrow wavelength excels at detecting sparse particles, making it particularly effective for snow and winter precipitation surveillance. Its compact size also makes it the natural choice for mobile applications, transportable deployments, and research operations.

The trade-off is range: X-band signals attenuate significantly in heavy rain, limiting effective observation to approximately 60 km. This makes X-band best suited as a gap-fill radar to supplement an existing S or C-band network, or for specialized research purposes where high resolution at short range is the priority.

- **Best for:** mobile and transportable deployments, research applications, gap-fill in existing networks, snow and winter precipitation
- **Transmitter:** magnetron (300 kW)
- **Typical range:** 60 km observation, 30 km QPE

Band Comparison at a Glance

Parameter	S-Band	C-Band	X-Band
Observation Range	460 km	230 km	60 km
Rain Fade / Attenuation	Least affected	Significantly more than S-Band	Highest
QPE Estimation Range	230 km	115 km	30 km
Best for Flooding / Heavy Rain	Yes — ideal	Good	Limited range
Relative Cost	Higher	Mid-range	Lower
Transmitter Type	Klystron (up to 1 MW)	Klystron, Magnetron, or solid-state	Magnetron (300 kW)

Dual-Polarization: The Data Quality Multiplier

While conventional radar transmits linear horizontally polarized pulses, dual-polarization radar systems transmit horizontally and vertically polarized pulses simultaneously. By sampling received echoes along both polarizations, the radar processor can analyze hydrometeor returns in a cross-section, providing far more accurate precipitation measurements, as well as hail and tornado debris detection. Additionally, non-meteorological phenomena like smoke plumes and bird/insect migrations can be identified and tracked. For operational meteorology, the practical value is significant:

- Accurate distinction between heavy rain and hail — critical for flood versus hail damage forecasting
- Better quantification of flooding extent and rain rate at range
- Increased accuracy in winter precipitation type forecasting (snow, sleet, freezing rain, rain)
- Highly accurate detection of lofted tornado debris — a direct life-safety application
- Identification of non-meteorological returns: smoke plumes, bird and insect migrations

Dual-pol data also feeds a suite of derived value-added products that extend the operational utility of the raw radar data significantly. Baron offers dual-pol configurations across S, C, and X-band systems.

What Makes Baron Radars Different

Baron has been designing and building weather radar systems for over 30 years, with more than 350 radars sold, installed, and upgraded worldwide — including for the U.S. National Weather Service. That experience is embedded in a set of proprietary technologies not available on any other radar platform.

ClearScan™ — AI-Powered Data Quality Algorithm

ClearScan™ is Baron's patent-pending data quality algorithm that goes beyond traditional clutter suppression. It identifies and removes a broad range of non-meteorological returns, including ground clutter, buildings, cellular towers, and Wi-Fi interference, with greater accuracy and less collateral data loss than conventional approaches. The result (Fig. 6) is cleaner base data and more confident analysis across a wide range of environmental conditions.




Figure 6 - ClearScan

CLEAN-AP — Oklahoma University Algorithm

Developed in partnership with the University of Oklahoma, CLEAN-AP (Clutter Environment Analysis using Adaptive Processing) is an advanced signal processing algorithm focused specifically on ground clutter suppression. It adaptively filters ground returns based on the specific environmental conditions at each radar site. It is exclusive to Baron radar systems.

Baron Calibration and Multi-Radial ZDR Calibration

Accurate calibration is the foundation of reliable quantitative precipitation estimation (QPE). Baron's proprietary calibration methods, including multi-radial differential reflectivity (ZDR) calibration, maintain measurement accuracy over time and across variable environmental conditions, directly improving the downstream products that agencies rely on for warnings and forecasting.

Open Data Architecture

Baron radar systems are built on open data standards, enabling seamless integration with existing meteorological software, numerical weather prediction (NWP) model ingestion pipelines, and third-party data systems. Organizations are not locked into proprietary data formats or display ecosystems.

Site Selection: The Factor That Overrides Everything Else

Of all the considerations in this guide, site selection has the greatest single impact on radar performance. A state-of-the-art radar placed in a suboptimal location will consistently underperform a more modest system sited correctly. Terrain, obstructions, and the geometry between the radar and the monitored area are not variables that technology can fully compensate for.

The Obstruction Problem

Mountains, large buildings, cellular towers, and other vertical obstructions block or scatter the radar signal, creating permanent blind sectors in the coverage area. In some terrain, no single site will provide complete coverage, requiring network design with multiple units or mobile supplements. Baron's site survey process identifies these limitations before installation, not after.



Figure 7 - Proper positioning of the radar means that the focus of the signal is over the observed area.

The Distance Problem

Radar signals rise in altitude as they travel from the antenna. At the correct distance, approximately 30 miles / 48 kilometers for most applications, the beam height over the monitored area is optimal for detecting precipitation at relevant altitudes. Too far, and the beam overshoots low-level weather. Too close, and the beam angle produces limited coverage with poor utility.

In mountainous or complex terrain where an ideal fixed site cannot be identified, a mobile or transportable radar configuration is often the most practical solution.

Baron Site Survey Process

Baron performs detailed pre-installation site surveys that determine optimal tower height, antenna tilt, and siting geometry for each specific deployment. The goal is a radar that delivers clean, accurate data free of terrain contamination from day one and that continues to perform without remediation for the lifetime of the system.

Sustainability and Total Cost of Ownership

A weather radar is a long-term infrastructure investment. Acquisition cost is only one component of total cost of ownership and often not the dominant one over a 20-year operating life. Baron designs its radar systems with long-term economics explicitly in mind.

- Klystron and magnetron transmitters designed for 20+ years of operational life with standard maintenance
- Automated performance monitoring provides real-time system health status and enables proactive maintenance
- Similar components across X, C, and S-band product lines reduce spare parts inventory and supply chain complexity
- Remote troubleshooting capability reduces the cost and delay of on-site service visits
- Minimal power consumption, comparable to a household microwave, reduces operational energy costs
- Recyclable transmitter components align with sustainability commitments

Baron also offers seamless upgrade paths, including dual-polarization retrofits and magnetron to solid-state conversions, that extend the operational life of existing radar investments rather than requiring full system replacement.

Parameter	Why it is important	S-Band	C-Band	X-Band
Sensitivity: Clear Air	Allows for the ability to detect sea breezes, dust storms, light precipitation	Least *	More than S-Band *	Most
Sensitivity: Precipitation	Ability to detect all types of precipitation	Most	More than X-Band *	Least *
Typical Observation Range	How far the radar can effectively detect	460 km	230 km	60 km
Atmospheric Attenuation Impact	Pulses can be absorbed or scattered by the atmosphere affecting your ability to accurately determine returns	Least	More than S-Band	Most
Attenuation Due to Precipitation Impact	Pulses can be absorbed or scattered by the precipitation surrounding the radar especially when the rain rate is high	Least *	Significantly more than S-Band *	Significantly more than C-Band *
Attenuation Due to Radome	Pulses can be absorbed or scattered by rain that has accumulated on the Radome	Least *	More than S-Band *	Most *
Ease of Base Data Interpretation	Necessary for accurately determining the hydrometeor type and rainfall rate estimation	Easiest	Challenging due to resonance effects *	Easy *
Hydrometeor Classification	Ability of the radar to determine what is causing the scattering in its field of view	Easiest	Challenging due to resonance effects and attenuation *	Easier than C-Band but attenuation effects need to be mitigated *
QPE Estimation Range	Effective range at which accurate Rain Rate can be estimated	230 km	115 km	30 km
Velocity De-Aliasing	Ability of radar to accurately track storms	Easiest	Easier than X-Band *	Challenging *
KDP Estimation (KDP μ 1/λ)	Ability of radar to accurately estimate rain rate using specific differential phase	Challenging during light rain *	Better than S-Band *	Most accurate and can be used for all rain rates

*Mitigation strategies available within the Baron Radar Systems.

Making the Right Decision

No two radar deployments are alike. The right system depends on your geography, your threat environment, your data requirements, and your long-term goals. Working through those variables with an experienced partner early in the process makes all the difference.

Baron's team of radar scientists and engineers has supported more than 350 deployments across every major climate and terrain type worldwide. We offer expert consultation, detailed site surveys, and configuration analysis because we believe the right match benefits both the customer and the mission.



Figure 8 - Baron delivered this C-band dual-polarization radar to the U.S. Department of Energy.

Ready to Start the Conversation?

Contact Baron's radar team to discuss your coverage requirements, environment, and budget. We'll help you identify the right configuration and perform a site survey before any commitment is made.

baronweather.com | solutions@baronweather.com | +1 (256) 881-8811

©2026 Baron Weather, Inc. All rights reserved. Baron and the Baron logo are registered trademarks of Baron Weather, Inc. Other trademarks are property of their respective owners. 10-2026.